

## SPECIFICATIONS

## HOOK INFORMATION:

Material: Nylon, 8 mil monofilament top yarn with Acrylic binder  
 Color: Please contact your sales rep for more information.

## CLOSURE INFORMATION

Tape Width (inches)	Shear Strength (Pounds)	Peel Strength
5/8	14.3	0.55 lb
3/4	17.6	0.70 lb
1	22.0	0.88 lb
1¼	26.4	0.99 lb
1½	33.0	1.32 lb
2	44.0	1.76 lb
4	88.0	3.52 lb

## PHYSICAL &amp; CHEMICAL CHARACTERISTICS

Resistance to heat	Softening point 180°C, melting point 215-220°C.	
Resistance to cold	No change at -30°C for 5 hours	
Resistance to water	Retain 50% of closure strength in water and recovers 100% of strength after drying	
Resistance to chemical	Alkalis	Resistant to 50% caustic soda, and 28% ammonia solutions
	Acids	Resistant to 7% Hydrochloric acid, 20% sulphuric acid and 10% nitric acid solutions
Influence of insects, mold	Not affected	
Influence of humidity	In humidity over 90% RH, closure strength is somewhat reduced	

For more information on GLT Products, please visit us online at [www.gltproducts.com](http://www.gltproducts.com) or call toll-free at **1-800-874-1748**.



## HEADQUARTERS:

6810 Cochran Road | Solon, OH 44139 | 440.914.1122 | 440.914.1133 Fax | **1.800.874.1748**

## DISTRIBUTION CENTERS:

**Ohio:** 6810 Cochran Road | Solon, OH 44139 | 440.914.1122  
**Texas:** 2902 East 13th Street, Suite 200 | LaPorte, TX 77571 | 713-670-9700  
**North Carolina:** 109 Sands Road | Reidsville, NC 27320 | 1.800.551.9760  
**California:** 4113 Gold River Lane | Stockton, CA 95215 | 1.800.833.4500