

SPECIFICATIONS

Fiberglass scrim is available in tape and cloth options. Both options are also manufactured with an adhesive backer (Sticky FAB) and can be used in various construction applications, such as drywall and plaster applications.

These products are also used in industrial insulation applications as a reinforcement for mastics and coatings over insulation.

Technical Information

Property	Test Results	Specifications	Test Method as per ASTM D-1668
Thickness (inch)	.0085	.0080 +/- .001	Method 5030
Weight (oz/yd.2)	1.96	1.80 - 2.15	Method 5041
Fabric Count			
ends	10	10 +/-2	Method 5050
picks	10	10 +/-2	
Finish Level (%)	20.6	17 – 22	ASTM D-578
Yarn			
Warp		G-150 1/0	
Fill		G-75	
Breaking strenght			Method 5100
Warps (lbs./in)	97	75 minimum	
Fill (lbs./in)	112	60 minimum	
Horizontal Pull*	23' 45"	Minimum 6 minutes	



Ordering Information

- 6 x 6 White 38" x 150' Fabglass Scrim Cloth
- 10x10 Black 36" x 150' Fabglass Scrim Cloth
- 10x10 White 2", 3" and 4" x 150' Fabglass Scrim Cloth
- 10x10 White 36" x 150' Fabglass Scrim Cloth
- 20x10 Black 36" x 150' Fabglass Scrim Cloth
- 20x10 White 2" and 3" x 150' Fabglass Scrim Cloth
- 20x10 White 36" x 150' Fabglass Scrim Cloth
- 10x10 White 2", 3" and 4" x 150' Fabglass Scrim Cloth with Adhesive

For more information on GLT Products, please call toll-free at 800.874.1748 or online at www.gltproducts.com.



Innovative Insulation Systems

HEADQUARTERS:

6810 Cochran Road | Solon OH 44139 | 440.914.1122 | 440.914.1133 Fax | **1.800.874.1748**

DISTRIBUTION CENTERS:

Ohio: 6810 Cochran Road | Solon OH 44139 | 440.914.1122

Texas: 8905 Market Street | Houston, TX 77029 | 1.800.874.1748

North Carolina: 501 West Camel Street | Greensboro, NC 27401 | 1.800.551.9760

California: 4113 Gold River Lane | Stockton, CA 95215 | 1.800.833.4500

Ontario, Canada: 55 Milburn Road | Hamilton, ON L8E 3C4 | 1.800.874.1748